

## LW EK3500V2

The EK Series is the result of an in depth study, in order to reach the best compromise between economy and performance, taking advantage of the latest improvements in automated mixed surface mount and through whole electronic assembly.

The EK Series is a project based on an upside down mono-block approach offering an all-in-one power module that contains the entire amplifier assembly.

Simplicity and effectiveness run hand by hand through the entire design to obtain an effectively skilled and workable product. The last generation Quanta-Pulse switching power supply reaches a new level of refined sensing and control of the power flow.

The cost-effective EK Series amplifiers are packed with solid and convincing arguments for the professionals searching for quality, reliability and value.



OUTPUT POWER 20Hz-20kHz, 0.1% THD				
@2 Ω	@4 Ω	@8 Ω	Bridge @4 Ω	Bridge @8 Ω
2 x 1500 W	2 x 1470 W	2 x 1300 W	3000 W	2940 W

Output Power Continuous Average Power RMS, 1kHz, 1.0% THD+N		
@2 Ω	2 x 1800 W	
@4 Ω	2 x 1750 W	
@8 Ω	2 x 920 W	
Bridge @4 Ω	3600 W	
Bridge @8 Ω	3500 W	
Pink Noise 12dB Crest Factor		
@2 Ω		
@4 Ω		
@8 Ω		
Frequency Response		
Power Bandwidth ±0.25dB	20Hz-20Khz.	
Phase Response		
@ 1 watt 20Hz-20kHz		
Total Harmonic Distortion		
20Hz-20kHz	<0,05%	
Damping Factor		
20Hz-500Hz @8 Ω	>400	

Intermodulation Distortion				
SMPTE				
Crosstalk				
20Hz-20kHz	> 75dB			
Voltage Gain	32 dB			
Sensitivity				
Rated Power @8 Ω				
Signal-to-Noise-Ratio				
Unweighted				
A weighted				
Required AC Mains 230 V - 50 Hz (idle)				
@4 Ω (1/8 rated power)				
@8 Ω (1/8 rated power)				
Dimensions				
W x H x D (mm)	483 x 89 x 250			
W x H x D (inches)	19 x 3.5 x 9.84			
Weight				
Net	6kg			